



## Back-UPS 650 Specifications

Model Number	BX650LI-MS
<b>Output</b>	
Output Capacity	650 VA / 325 Watts
Output Voltage / Frequency (On utility)	230V / 45-65 Hz
Output Voltage / Frequency (On battery)	230V +/-10%, 50 or 60 Hz +/-1 Hz (auto-sensing)
Output Connections	2 Universal outlets (both with battery backup and surge protection)
Waveform Type	Stepped Approximation to Sine Wave
<b>Input</b>	
Input Voltage / Frequency	170 - 280 V / 50/60Hz +/-1Hz (default:50Hz)
Input Connection	NEMA 5-15P
<b>Surge Protection</b>	
AC Power Surge Protection	All outlets
<b>Physical</b>	
Unit Dimensions (H x W x D)	142 x 101 x 300 mm
Unit Weight	4.4 Kg
Shipping Dimensions (H x W x D)	223 x 143 x 347 mm
Shipping Weight	4.6 Kg
Color	Black
UPC Code	731304318187
<b>Battery</b>	
Battery Type	Maintenance-free, sealed lead-acid battery, leak proof
Battery Size	12 volt, 7 Ah
<b>Management</b>	
Alarms	Visual (LED) and audible alarms
Adjustable Sensitivity and Transfer Voltage	Low, Medium (default), High

**APC by Schneider Electric**

132 Fairgrounds Rd  
West Kingston, RI 02892

[www.apc.com](http://www.apc.com)

**APC**<sup>®</sup>  
by Schneider Electric