



Overview

HP Z24n 24-inch Narrow Bezel IPS Display



- 1. Menu button
- 2. Luminance
- 3. Color control

- 4. Input control
- 5. Information
- 6. Power button/LED



- 1. Master power switch
- 2. Power connector
- 3. Audio output 3.5 mm
- 4. DVI-D
- 5. HDMI v 1.4 input (MHL 2.0)

- 6. Mini-DisplayPort
- 7. DisplayPort v 1.2 in
- 8. DisplayPort v 1.2 out
- 9. (4) USB 3.0 downstream ports (one fast charging)
- 10. (1) USB 3.0 upstream port

Overview

Overview

Create a seamless multi-display¹ array with the virtually borderless HP Z24n 24-inch Narrow Bezel IPS Display, which also delivers factory color calibration and flexible connectivity.

Key features:

- Enjoy stunning high resolution and a three-sided borderless design that maximizes the screen and enables seamless tiling of multiple displays.¹
- Count on a factory-calibrated 99% sRGB color gamut for reliable, accurate color between displays and projects.
- Connect to multiple display and devices with a range of integrated ports right at the display.
- Use picture-in-picture or picture-by-picture to boost your multi-tasking productivity.
- Work comfortably with customizable tilt, height adjustment, swivel, and pivot settings.
- Get world-class service and support, and extend your protection with optional HP Care Packs.²
- Reduce power consumption and help lower your costs with an energy-efficient design.

¹ Each display sold separately.

² Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Technical Specifications

Models: K7B99A4

Panel	Type	24-inch IPS w/LED backlight
	Viewable Image Area (diagonal)	61,13 cm (24-inch) widescreen; diagonally measured
	Panel Active Area (W x H)	51,84 x 32,4 cm (20.41 x 12.75 in)
	Resolution	1920 x 1200 @ 60 Hz
	Aspect Ratio	16:10
	Viewing Angle	Up to 178° horizontal/178° vertical typical
	Brightness	300 cd/m ²
	Contrast Ratio (Typical)	1000:1 Static; 5,000,000:1 Dynamic (DCR)
	Response Times*	14 ms typical (G-to-G); 8ms with scalar overdrive
	Pixel Pitch	0.270 mm
	Pixels Per Inch (PPI)	94.3 DPI
	Backlight Lamp Life (to half brightness)	30,000 hours minimum
	Color Gamut	Up to 16.7 million colors with the use of FRC technology
	Color Gamut (Typical)	99% sRGB

* Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

User Controls	Buttons or Switches	Menu, Luminance, Color Control, Input Control, Information
	User Programmable Modes	20
	Languages	10 (German, S-Chinese, T-Chinese, Japanese, English, Spanish, French, Italian, Netherlands and Portuguese)
	On Screen Display (OSD) User Controls	Luminance, Color control, Input control, Image Control, PIP control, Power control, OSD Control, Management, Language, Information
	Audio Controls	N/A
Signal Interface/ Performance	Horizontal Frequency	30 - 75 kHz
	Vertical Frequency	50 - 60 Hz
	Native Resolution	1920 x 1200 @ 60 Hz
	Preset Graphic Modes (non-interlaced)	640 x 480 @ 60Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 1024 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1600 x 1200 @ 60 Hz 1680 x 1050 @ 60 Hz

Technical Specifications

		1920 x 1080 @ 60 Hz	
		1920 x 1200 @ 60 Hz	
Video/Other Inputs	Maximum Pixel Clock Speed	170 MHz	
	Anti-Glare	Yes	
	Plug and Play	Yes	
	Input/Output Connectors	(1) DVI-D (1) MHL 2.0 ¹ /HDMI 1.4 (1) DisplayPort 1.2, (1) Mini-DisplayPort, (1) DisplayPort 1.2 out HDCP support on all inputs	
	USB	4 USB 3.0 [4 downstream (one fast charging), 1 upstream]	
Multimedia	Video Cables Included	(1) DisplayPort 1,8 m (5.9 ft) (1) Mini-DisplayPort 1,8 m (5.9 ft) (1) USB 3.0 1,8 m (5.9 ft)	
	Audio	(1) Audio output 3.5mm	
	Speakers	N/A	
Power	Power Supply	Internal	
	Input Power	100 - 240 VAC 50/60 Hz	
	Maximum Power	70 W	
	Typical Power	36 W	
	Sleep Power	0.5W (standby)	
	Power Cable Length	1,8 m (5.9 ft)	
	Mechanical	Dimensions (W × D × H)	Unpacked w/stand
Unpacked w/o stand (head only)			53.38 x 4.93 x 35.11 cm (21.01 x 1.94 x 13.82 in)
Packaged			63.2 x 25 x 44 cm (24.88 x 9.84 x 17.32 in)
Weight		Head Only	3,87 kg (8.51 lb)
		Unpacked	5,78 kg (12.71 lb)
		Packaged	7,38 kg (16.25 lb)
Ergonomic Features		Detachable Stand	Yes, ships detached
	Height Adjustment	Yes, 130 +/-3 mm	
	Tilt Range	-5° to + 22° vertical	
	Swivel	Yes, 45° +/-2°	
	Pivot	Yes, 90°	
Environmental	Quick Release⁵	HP QR2 quick release included	
	Temperature - Operating	5° to 35° C (41° to 95° F)	
	Temperature - Non-operating	-20° to 60° C (-4° to 140° F)	

Technical Specifications

	Humidity - Operating	20% to 80% non-condensing
	Humidity - Non-operating	5% to 95%, 38.7° C max wet-bulb
	Altitude - Operating	0 to 5,000 m (0 to 16,404 ft)
	Altitude - Non-operating	0 to 12,192 m (0 to 40,000 ft)
	White LED Backlights	Yes
	CCFL Panel	No
	Arsenic-Free Display Glass	Yes
	Low Halogen²	Yes (except cables)
	Mercury-Free Display Backlighting	Yes
Options	HP LCD Speaker Bar —Part number NQ576AA	Powered directly by the connected PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors. Features include dual speakers with full sound range and dual external headphone jacks. Sold separately. For more information, refer to the product's QuickSpecs.
	HP Single Monitor Arm —Part number BT861AA	The flexible design of the HP Single Monitor Arm provides a seemingly endless range of display adjustments with an amazing 13 inches of lift, 75 degrees of tilt, and 360 degrees of pan and rotation – all at your fingertips -- helping you stay comfortable and productive throughout the day.
	HP DisplayPort Cable Kit —Part number VN567AA	Connects a DisplayPort connector on an HP Business Desktop computer to a DisplayPort connector on a monitor
	HP Quick Release Bracket —Part number EM870AA ⁵	An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document.
	HP Business PC Security Lock Kit —Part number PV606AA	Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point.
What's in the box?	Monitor and Accessories	HP Z24n 24-inch Narrow Bezel IPS Display, AC power cord 1,8 m (5.9 ft), DisplayPort cable 1,8 m (5.9 ft), Mini-DisplayPort cable 1,8 m (5.9 ft), USB 3.0 cable 1,8 m (5.9 ft)
	Documentation	CD (includes user guide, warranty, drivers)
	Software	HP Display Assistant
Other	User Guide Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	Warranty Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	Color	Black

Technical Specifications

VESA Mounting	100 mm VESA mount
Security Lock-Ready	Yes
Country of Origin	China
Certification and Compliance	TCO Certified, TCO Certified EDGE, CEL Grade 1, ENERGY STAR® Qualified, EPEAT® Gold ³ , CB, TUV/GS, TUV/Ergo, TUV-S, UL, CCC, CECP, SEPA, BSMI, CE, FCC(Canada), BSMI ,KC ,VCCI ,C-Tick, Microsoft WHQL Certification (Windows 8.1, Windows 8, and Windows 7); SmartWay Transport Partnership (NA)
Compatibility	Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.
Service and Warranty	Protected by HP, including a 3 year standard limited warranty. Optional HP Care Pack Services are extended service contracts that extend your protection beyond the standard warranties. ⁴

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR® and the ENERGY STAR® mark are registered trademarks of the U.S. Environmental Protection Agency.

1. MHL 2.0 port will charge a MHL compatible smart phone and tablet battery. Requires the smart phone or tablet to be enabled for MHL or have an HDMI dongle to connect to the monitor. See your mobile device specifications.
2. Power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
3. EPEAT® registered where applicable. EPEAT® registration varies by country. See www.epeat.net for registration status in your country.
4. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply. See www.hp.com/go/cpc for details.
5. The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) for all devices mounted. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.

